An Indoor Positioning System Using Ultra-Wideband Technology

Nông Thế Lâm
Thai Nguyen University of Information and Communication Technology
Thai Nguyen University, Thai Nguyen, Vietnam
student552@ictu.edu.vn

***Abstract*—This undergraduate thesis investigates an indoor positioning system based on ultra-wideband radio. Indoor navigation needs a way to estimate position where satellite signals may be unavailable or unreliable. The student reviews indoor positioning, designs and fabricates positioning nodes, programs node algorithms, and connects the devices into a working system. The report includes circuit, software, and integration material. The conclusion reports a functioning set of positioning nodes and a combined system with results the author considers promising for indoor robots or autonomous vehicles. The manuscript does not establish a general accuracy guarantee across buildings. Positioning quality can change with obstacles, node placement, radio interference, and calibration. The author calls for better accuracy and stability, and describes parking maps and autonomous navigation as later applications. The contribution is a documented student study or prototype whose stated scope can guide further testing.**

***Index Terms*—ultra-wideband, indoor positioning, radio nodes, embedded systems**

I. Introduction

Indoor navigation needs a way to estimate position where satellite signals may be unavailable or unreliable. This thesis investigates an indoor positioning system based on ultra-wideband radio. It begins from a practical engineering need and explains the technologies and workflow chosen for the case. The objective is to document a student implementation or comparative investigation, together with the evidence available in the manuscript. Broader operational or economic effects require separate measurements and are not assumed from the existence of a prototype [1]. Related published studies provide context for the subject and methods [2], [3], [4], [5], [6], [7], [8], [9], [10]. These contextual works were selected for this English summary; they are not asserted to appear in the original thesis bibliography.

II. Methods

The student reviews indoor positioning, designs and fabricates positioning nodes, programs node algorithms, and connects the devices into a working system. The report includes circuit, software, and integration material. The source is summarized through its stated design, implementation material, examples, and conclusion. Features shown in the manuscript are distinguished from proposals for later development. This review does not add a new experiment, fill missing measurements with estimates, or treat a planned capability as an observed result. The source thesis remains the provenance for the reported work [1].

Supervisor: Phạm Xuân Kiên, Thai Nguyen University of Information and Communication Technology (pxkien@ictu.edu.vn).

III. Results

The conclusion reports a functioning set of positioning nodes and a combined system with results the author considers promising for indoor robots or autonomous vehicles. The manuscript does not establish a general accuracy guarantee across buildings. The report's screens, configurations, examples, or measurements constitute the evidence for this summary. A capability described only as a design intention is not counted as a validated operational outcome. No additional performance, adoption, financial, or safety figure has been introduced here. The result is interpreted within the scope of the student's documented setup [1].

IV. Discussion

Positioning quality can change with obstacles, node placement, radio interference, and calibration. The author calls for better accuracy and stability, and describes parking maps and autonomous navigation as later applications. Further evaluation could measure error distributions and system stability under documented node layouts and realistic indoor conditions before use for vehicle guidance. These limitations affect how the evidence should be read. The current manuscript can support understanding of the design and reported demonstration, while independent tests would be needed for stronger claims. Any later deployment should document its environment and separate observed outcomes from intended benefits [1].

V. Conclusion

The thesis documents an indoor positioning system based on ultra-wideband radio. The conclusion reports a functioning set of positioning nodes and a combined system with results the author considers promising for indoor robots or autonomous vehicles. The manuscript does not establish a general accuracy guarantee across buildings. Positioning quality can change with obstacles, node placement, radio interference, and calibration. The author calls for better accuracy and stability, and describes parking maps and autonomous navigation as later applications. Further evaluation could measure error distributions and system stability under documented node layouts and

realistic indoor conditions before use for vehicle guidance. Accordingly, the present contribution is a source-grounded account of the student work and its tested or illustrated scope. Claims about broader effectiveness should be assessed in later work using explicit evaluation conditions [1].

References

[1] Nông Thế Lâm, ”An Indoor Positioning System Using Ultra-Wideband Technology,” internal undergraduate thesis (original in Vietnamese), Thai Nguyen University of Information and Communication Technology, 2024.

[2] Abdulrahman Alarifi et al., ”Ultra Wideband Indoor Positioning Technologies: Analysis and Recent Advances,” Sensors, 2016. doi:10.3390/s16050707.

[3] Ominik Gnaś, ”Precise indoor location system using Ultra-Wideband technology,” PRZEGLĄD ELEKTROTECHNICZNY, 2023. doi:10.15199/48.2023.01.54.

[4] Alessio De Angelis et al., ”Indoor Positioning by Ultrawide Band Radio Aided Inertial Navigation,” Metrology and Measurement Systems, 2010. doi:10.2478/v10178-010-0038-0.

[5] Zuin Silvia et al., ”Ultra Wide Band Indoor Positioning System: analysis and testing of an IPS technology,” IFAC-PapersOnLine, 2018. doi:10.1016/j.ifacol.2018.08.292.

[6] Yinzhi Zhao et al., ”A Novel Ultra-Wideband Double Difference Indoor Positioning Method with Additional Baseline Constraint,” ISPRS International Journal of Geo-Information, 2021. doi:10.3390/ijgi10100634.

[7] Weixiong Wan et al., ”Ultra-wideband indoor dynamic target positioning system,” Journal of Physics: Conference Series, 2022. doi:10.1088/1742-6596/2170/1/012048.

[8] Paul Schwarzbach et al., ”Statistical Evaluation and Synthetic Generation of Ultra-Wideband Distance Measurements for Indoor Positioning Systems,” IEEE Sensors Journal, 2022. doi:10.1109/jsen.2021.3121627.

[9] M. Segura et al., ”Ultra wideband indoor navigation system,” IET Radar, Sonar & Navigation, 2012. doi:10.1049/iet-rsn.2011.0352.

[10] Benjamin Waldmann et al., ”A Pulsed Frequency Modulated Ultra Wideband Technique for Indoor Positioning Systems,” Frequenz, 2008. doi:10.1515/freq.2008.62.7-8.195.